# Volumetric Image Analysis for Ultrasonic Inspection Automation

R. David Obenauf





### **Ultrasonic Inspection**

#### An Introduction to Non-Destructive Acoustic Evaluation

- Traditional Ultrasound Imaging Techniques
  - Data collection
  - Displaying data and finding indications
  - Limitations
  - How can we use computers to do the hard work for us?
- UT Inspection Automation and CloudView
  - Algorithmic process to find relevant data
  - Finding and reporting flaws
  - Limitations and further development



## **Ultrasonic Inspection Techniques**

### Finding and Reporting Indications

#### Ultrasonic Transmission

- Acoustic waves propagate well through solids
- Waves reflect on impedance mismatches

#### Indications

- Manufacturing defects cause reflections
- Interior features can be seen as well


#### Reporting Flaws

- Inspection of captured data can highlight flaws
- Data can be reported to customers for further analysis
- Manufacturing can be improved or changed



### **Traditional Methods**


A-Scans, C-Scans



### **Traditional Methods**

#### A-Scans, B-Scans, C-Scans

- C-Scans display extrema of an A-scan in a 2D space
- Indications show as  $max(|P_{(x,y,t)}|)$  is relatively large



#### Gates must be well-chosen to find indications


### **Automation and CloudView**

#### Finding and Reporting Indications

- Gating Interior Volume
  - Finding the front and back wall
  - Mitigating 'holes'
- Classifying Indications
  - Pulse nature
  - Signal Techniques
- Presentation of Data
  - Validation of Results
  - Sorting and Reporting
- Further Considerations




## Gating




- Variable thresholds allow for tuning based on the acquired data
- Visual presentation gives user feedback


#### Holes in the data




- Gate Thresholding fails on weak signals, leaving holes in the results
- Data can be interpolated to fill in the gaps

### Holes in the data






### Filling in the Holes



- Gate start and stop yield two 'images'
- Interpolation, smoothing, and comparison with an anticipated shape corrects the gate

### Filling in the Holes


 Fixing the Gate allows us to 'see' inside the part



 Maxima within the new region can be examined

## **Finding Significant Features**

### **Amplitude Analysis**




- Enveloping the magnitude of the function shows us peaks
- Reduces ripple in results, Blobs are contiguous

## **Finding Significant Indications**

### **Blob Analysis**


- Indications are 'louder' than their surroundings
- Statistical thresholding picks out significant features



## **Finding Significant Indications**

#### Automation with CloudView

- Points are found by thresholding above a chosen bin amplitude
- Points can then be sorted into blobs and highlighted as indications for further analysis



### **Automation and CloudView**

#### Further Development

- Blob Analysis
  - Sort points into groups
  - Capture the data within a group
- Reporting
  - Automate report generation
  - Getting and presenting data snippets
- Further Selection Criteria
  - Cleaning signals
  - Finding obfuscated reflections
  - Characterizing type of indication
- Porting to other languages

## **Volumetric Ultrasonic Analysis**

#### In Conclusion

- Traditional Ultrasonic Data Interpretation
  - Robust
  - Time consuming, error prone

#### Proposed Solution

- Signal Analysis techniques can automate indication-hunting process
- Image Analysis can be used on the resulting data to automate reporting and characterization, saving inspectors and customers time

### Further Development

- Implement Blob sorting algorithm
- Generate automatic reports with data voxels
- Hone the indication segmentation process, characterize flaws in-place

